



Storm Water BMP Requirements Applicability Form (Storm Water Intake Form for all Development Permit Applications)		Form I-1	
Project Information			
Project Title:			
Project Address/Location:			
Brief Description of Work Proposed:			
Determination of Requirements			
Answer each step below, starting with Step 1 and progressing through each step until reaching "Stop". <b>Upon reaching a Stop, do not complete further Steps beyond the Stop.</b>			
Step	Answer	Progression	
<b>Step 1:</b> Does the project consist exclusively of one or both of the activity types below? <ul style="list-style-type: none"> <li>Project with no soil disturbance or change to building general exterior dimensions or structural framing. <i>Examples:</i> interior remodeling, electrical work, HVAC work, plumbing, etc.</li> <li>Routine maintenance. <i>Examples:</i> roof repairs, pavement repairs or resurfacing, resurfacing or repairing existing sidewalks or pedestrian ramps, trenching and resurfacing associated with utility work, or rebuilding a structure to its original design after a fire or natural disaster.</li> </ul>	<input type="checkbox"/> Yes	<b>STOP.</b> Project is <u>Exempt</u> No permanent storm water BMP plan is required. <ul style="list-style-type: none"> <li>Interior projects are not subject storm water requirements.</li> <li>Outdoor, routine maintenance projects not requiring a grading plan must include the standard "Construction Storm Water BMP Notes" on their site plans.</li> </ul>	
	<input type="checkbox"/> No	Go to Step 2.	
<b>Step 2:</b> Does the project create or replace <u>less</u> than 2,500 square feet of impervious area (rooftop or pavement, including roads, sidewalks, parking lots, concrete patios, etc.) <u>AND</u> is also not an automotive repair shop or a retail gasoline outlet?	<input type="checkbox"/> Yes	<b>STOP.</b> Project is a <u>Standard Project</u> Incorporate "Permanent Storm Water BMP Notes" into site plan. If no grading plan is required also include "Construction Storm Water BMP Notes."	
	<input type="checkbox"/> No	Complete and attach Form I-2.	
Certification			
Name of Person Completing Form			
Role	Phone		
Company	Email		
Signature			Date
Owner Contact Information (if different from above signatory)			
Name			
Email			
Company	Phone		

The following construction BMP notes shall be added to the site plan as determined in the



completion of forms I-1 and I-2:

Construction Storm Water BMP Notes

1. All applicable construction BMPs and non-storm water discharge BMPs shall be implemented in accordance with the City of National City minimum BMP requirements included in the National City Municipal Code and the City of National City Jurisdictional Runoff Management Program (JRMP). All storm water BMPs shall be maintained for the duration of the project.
2. Erosion control BMPs shall be implemented for all portions of the project area in which no work has been done or is planned to be done over a period of 14 or more days. All onsite drainage pathways that convey concentrated flows shall be stabilized to prevent erosion.
3. Run-on from areas outside the project area shall be diverted around work areas to the extent feasible. Run-on that cannot be diverted shall be managed using appropriate erosion and sediment control BMPs.
4. Sediment control BMPs shall be implemented, including providing fiber rolls, gravel bags, or other equally effective BMPs around the perimeter of the project to prevent transport of soil and sediment offsite. Any sediment tracked onto offsite paved areas shall be removed via sweeping at least daily. All BMPs shall be installed and maintained in accordance with the applicable CASQA fact sheets.
5. Trash and other construction wastes shall be placed in a designated area at least daily and shall be disposed of in accordance with applicable requirements.
6. Materials shall be stored to avoid being transported in storm water runoff and non-storm water discharges. Concrete washout shall be directed to a washout area designed in accordance with CASQA standards; concrete shall not be washed out to the ground.
7. Stockpiles and other sources of pollutants shall be covered when the chance of rain within the next 48 hours is at least 50%.

The following post-construction (permanent) BMP notes listed shall be added to the site plan for all Standard Projects, except where not applicable and feasible as determined by the City of National City.

Permanent Storm Water BMP Notes

1. Landscaped areas shall be designed in accordance with Water Efficient Landscape Ordinance requirements.
2. Roof drainage shall be directed to landscaped areas or rain barrels.
3. Walkways shall be designed to drain to adjacent landscaped or natural areas or constructed using permeable materials.
4. Streets, sidewalks, and parking lot aisles shall be constructed to the minimum width necessary, provided public safety is not compromised.
5. Existing trees and natural areas, including but not limited to natural water bodies and natural storage reservoirs or drainage corridors (e.g., topographic depressions, natural swales, and areas of naturally permeable soils), shall be conserved or otherwise protected to the extent feasible.



## City of National City Engineering

6. The impervious footprint, including roofed areas and paved areas, of the project shall be minimized to the extent applicable and feasible.
7. Dumpsters, other trash receptacles, and waste cooking oil containers shall be stored inside buildings or in four-sided enclosures with a structural overhead canopy designed to prevent precipitation from contacting materials stored in the enclosure.
8. Onsite storm drains shall be stenciled or otherwise permanently labeled with “No Dumping, Drains to Ocean” or other equivalent language approved by the City.
9. Outdoor material storage areas and outdoor work areas shall be protected from rainfall, run-on, and wind dispersal.



Storm Water BMP Requirements for Standard and Priority Development Projects		Form I-2
Project Information		
Project Title:		
Project Address/Location:		
The project is (select one): <input type="checkbox"/> New Development <input type="checkbox"/> Redevelopment <sup>†</sup>		
Project total disturbed area: _____ ft <sup>2</sup> (Note: 1 acre = 43,560 ft <sup>2</sup> )		
Total proposed newly created or replaced impervious area: _____ ft <sup>2</sup> (Impervious area includes rooftops and impermeable pavement, such as concrete or asphalt).		
Step 1. Identify Applicable Project Categories		
<i>Mark whether each of the following categories describes the proposed project by indicating "Yes" or "No".</i>		
1.1) New development projects that create 10,000 square feet or more of impervious surfaces (collectively over the entire project site). This includes commercial, industrial, residential, mixed-use, and public development projects on public or private land.	Yes <input type="checkbox"/>	No <input type="checkbox"/>
1.2) Redevelopment projects that create and/or replace 5,000 square feet or more of impervious surface (collectively over the entire project site on an existing site of 10,000 square feet or more of impervious surfaces). This includes commercial, industrial, residential, mixed-use, and public development projects on public or private land.	Yes <input type="checkbox"/>	No <input type="checkbox"/>
1.3) New and redevelopment projects that create and/or replace 5,000 square feet or more of impervious surface (collectively over the entire project site), and support one or more of the following uses: (i) Restaurants. This category is defined as a facility that sells prepared foods and drinks for consumption, including stationary lunch counters and refreshment stands selling prepared foods and drinks for immediate consumption (Standard Industrial Classification (SIC) code 5812). (ii) Hillside development projects. This category includes development on any natural slope that is twenty-five percent or greater. (iii) Parking lots. This category is defined as a land area or facility for the temporary parking or storage of motor vehicles used personally, for business, or for commerce. (iv) Streets, roads, highways, freeways, and driveways. This category is defined as any paved impervious surface used for the transportation of automobiles, trucks, motorcycles, and other vehicles. <i>Note that this does not include routine maintenance projects as noted on Form I-1 and defined in more detail in Chapter 1 of the BMP Design Manual.</i>	Yes <input type="checkbox"/>	No <input type="checkbox"/>

<sup>†</sup> Redevelopment is any land-disturbing activity that results in the creation, addition, or replacement of exterior impervious surface on a site on which some past development has occurred. Examples include the expansion of a building footprint, road widening, and the addition to or replacement of a structure. Replacement of impervious surfaces includes any activity where impervious material(s) are removed, exposing underlying soil during construction. Redevelopment does not include routine maintenance activities, such as trenching, and resurfacing associated with utility work; pavement grinding and resurfacing of existing roadways; construction of new sidewalk, pedestrian ramps, or bike lanes on existing roadways; or routine replacement of damaged pavement such as pothole repair.



Storm Water BMP Requirements for Standard and Priority Development Projects		Form I-2	
<p>1.4) New or redevelopment projects that create or replace 2,500 square feet or more of impervious surface (collectively over the entire project site), and discharging directly to an Environmentally Sensitive Area (ESA). “Discharging directly to” includes flow that is conveyed overland a distance of 200 feet or less from the project to the ESA, or conveyed in a pipe or open channel any distance as an isolated flow from the project to the ESA (i.e. not commingled with flows from adjacent lands).</p> <p><i>Note: a map of ESAs identified in the City of National City is available at the Engineering Counter and on the City’s storm water website. See manual Section 1.4.2 for additional guidance.</i></p>	Yes	No	
<p style="text-align: center;"><input type="checkbox"/></p> <p style="text-align: center;"><input type="checkbox"/></p>			
<p>1.5) New development projects of any size, or redevelopment projects that create and/or replace 5,000 square feet or more of impervious surface, that support one or more of the following uses:</p> <p>(i) Automotive repair shops. This category is defined as a facility categorized in any one of the following SIC codes: 5013, 5014, 5541, 7532-7534, or 7536-7539.</p> <p>(ii) Retail gasoline outlets (RGOs). This category includes RGOs that meet the following criteria: (a) 5,000 square feet or more or (b) a projected Average Daily Traffic (ADT) of 100 or more vehicles per day.</p>	Yes	No	
<p style="text-align: center;"><input type="checkbox"/></p> <p style="text-align: center;"><input type="checkbox"/></p>			
<p>1.6.a) New or redevelopment projects that result in the disturbance of one or more acres of land and are expected to generate pollutants after the completion of construction.</p> <p><i>Note: most projects are expected to generate pollutants after the completion of construction. If your project is at least one acre but you believe it will not generate pollutants after the completion of construction, include an explanation below in box 1.6.b. See BMP Design Manual Section 1.4.2 for additional guidance.</i></p>	Yes	No	
<p style="text-align: center;"><input type="checkbox"/></p> <p style="text-align: center;"><input type="checkbox"/></p>			
<p>1.6.b) <u>Explanation</u>, if marked “No” and project is at least one acre :</p>          			
<p><b>Are any of the categories above marked as “Yes”?</b></p> <p><input type="checkbox"/> Yes – Complete Step 2.</p> <p><input type="checkbox"/> No – <b>STOP.</b> The project is a <u>Standard Project</u>. Incorporate Permanent Storm Water BMP Notes into site plan. If no grading plan is required also include “Construction Storm Water BMP Notes.”</p>			



Stormwater BMP Requirements for Standard and Priority Development Projects	Form I-2
<b>Step 2. Priority Development Project (PDP) Exemptions</b>	
<i>Does the project consist exclusively of either of the activity types below?</i>	
2.1) New or retrofit paved sidewalks, bicycle lanes, or trails that meet any of the following criteria: (i) Designed and constructed to direct storm water runoff to adjacent vegetated areas, or other non-erodible permeable areas (ii) Designed and constructed to be hydraulically disconnected from paved streets or roads (iii) Designed and constructed with permeable pavements or surfaces. <i>(Routine maintenance is always exempt, see form I-1)</i>	<input type="checkbox"/> Yes – <b>STOP.</b> The project is a <u>Standard Project</u> . Incorporate Construction Storm Water BMP Notes and Permanent Storm Water BMP Notes into site plan.  <input type="checkbox"/> No. Answer box 2.2 below.
2.2) Retrofitting or redevelopment of existing paved alleys, streets or roads that are designed and constructed in accordance with the USEPA Green Streets guidance (see BMP Design Manual for details).	<input type="checkbox"/> Yes – <b>STOP.</b> The project is <u>not</u> a PDP but must meet Green Streets standards. Contact Engineering staff for details before proceeding with project design.  <input type="checkbox"/> No. The project is a <u>PDP*</u> . Go to Step 3.
<b>Step 3. Special Sizing for Redevelopment (Redevelopment Priority Development Projects only)</b>	
3.1) Is the project a redevelopment project?	<input type="checkbox"/> Yes. Complete box 3.2 below.  <input type="checkbox"/> No. Go to Step 4.
3.2) The area of existing (pre-project) impervious area at the project site is: _____ ft <sup>2</sup> (A) The total proposed newly created or replaced impervious area is _____ ft <sup>2</sup> (B) Percent impervious surface created or replaced, (B/A)*100 = _____ % The percent impervious surface created or replaced is (select one based on the above calculation):	<input type="checkbox"/> less than or equal to 50%. Only created/replaced impervious areas are considered <u>PDP*</u> . Continue to Step 4.  <input type="checkbox"/> greater than 50%. The entire project site is a <u>PDP*</u> . Continue to Step 4.

\* If the project does not require a grading permit, a "Construction BMP Plan for Priority Development Projects without Grading Permits" is required. Construction BMP Plan must also include the "Construction Storm Water BMP Notes."



Stormwater BMP Requirements for Standard and Priority Development Projects	Form I-2
<b>Step 4. Hydromodification Requirements (Priority Development Projects only)</b>	
<p>4.1) Does the project discharge storm water runoff to any of the following?</p> <p>(i) Existing underground storm drains discharging directly to water storage reservoirs, lakes, enclosed embayments (including San Diego Bay), or the Pacific Ocean</p> <p>(ii) Conveyance channels whose bed and bank are concrete lined all the way from the point of discharge to water storage reservoirs, lakes, enclosed embayments (including San Diego Bay), or the Pacific Ocean</p> <p>(iii) Existing underground storm drains or conveyance channels whose bed and bank are concrete lined all the way from the point of discharge to the Sweetwater River. <i>This exemption cannot be claimed until the San Diego Bay WQIP has been approved. Check with Engineering staff for details.</i></p>	<p><input type="checkbox"/> Yes – <b>STOP</b>. The project is a <u>PDP</u>* that is exempt from hydromodification (flow) control requirements. Prepare and submit SWQMP documenting project compliance with numeric sizing standards for pollution control requirements.</p> <p><input type="checkbox"/> No. Project is a <u>PDP</u>*. Answer the question in box 4.2 below to determine applicability of additional requirements. (At a minimum the project must meet numeric sizing standards for pollutant control <b>and</b> hydromodification (flow) control.)</p>
<p>4.2 Does protection of critical coarse sediment yield areas apply based on review of the Potential Critical Coarse Sediment Yield Area Map? <i>See the map on the City's Storm Water web page and at the Engineering Counter.</i></p>	<p><input type="checkbox"/> Yes – <b>STOP</b>. The project is a <u>PDP</u>*. Prepare and submit a SWQMP that meets sizing standards for pollutant control, hydromodification (flow) control and analysis of potential critical coarse sediment yield areas and associated management measures. See BMP Design Manual Section 6.2.</p> <p><input type="checkbox"/> No – <b>STOP</b>. The project is a <u>PDP</u>*. Prepare and submit a SWQMP that meets sizing standards for pollutant control, and hydromodification (flow) control.</p>

\* If the project does not require a grading permit, a "Construction BMP Plan for Priority Development Projects without Grading Permits" is required. Construction BMP Plan must also include the "Construction Storm Water BMP Notes."



## Construction BMP Plan for Priority Development Projects without Grading Permits

**Project Name or Address:** \_\_\_\_\_ **Permit ID:** \_\_\_\_\_

*Describe proposed BMPs below, and indicate where they will be used on the "Project Construction BMP Exhibit" on the next page.*

<b>BMP Category</b>	<b>BMP Description<sup>1</sup></b>	<b>Proposed? (Y/N/NA)</b>	<b>Description of How This BMP Will Be Used at the Project, or, if Not Applicable, Explain Why</b>
Perimeter Protection	Install BMPs around the perimeter of the work area to prevent dirt from leaving. Common BMPs used include fiber rolls, gravel bags, and silt fence.		
Erosion Control	Divert run-on from surrounding areas from running through disturbed areas, e.g., by using gravel bags or fiber rolls. Stabilize disturbed drainage pathways that run through the site where applicable.		
Inlet Protection	Install gravel bags or equivalent around onsite storm drains. <sup>2</sup>		
Waste Management	Collect and properly store trash and other waste materials at least daily. Regularly and properly dispose of wastes.		
Concrete Waste Management	Direct concrete washout to a designated washout area. <sup>3</sup> Discharge to the ground is not allowed.		
Material Storage	Cover materials that could be transported by runoff from rain. Use secondary containment for liquids. Provide fiber roll or equivalent around perimeter of stockpiles, and cover (e.g., with plastic sheeting) before storms.		
Sediment Tracking	Sweep paved areas adjacent to work area as necessary, at least daily, to remove accumulated or tracked sediment. If vehicles will enter the work area, install a stabilized construction entrance.		
Discharge Prevention	Do not allow any water other than rain water to discharge from the site. Maintain appropriate materials to address spills that may occur. Use drip pans to catch leaks from vehicles and equipment.		

1. This table is a simplified description of required BMPs intended for smaller projects that are completed relatively quickly. The City reserves the right to require additional BMPs in accordance with the Municipal Code and Section 2.1 of Appendix B of the City's JRMP where necessary.
2. See CASQA BMP SE-10.
3. See CASQA BMP WM-8.
4. See CASQA BMP TC-1.

**For additional information please visit:**

<http://www.nationalcityca.gov/index.aspx?page=568>



*Legend/ Standard Symbols*

—FR— Fiber roll	<table border="1"><tr><td>I</td></tr></table>	I	Inlet protection	<table border="1"><tr><td>WM</td></tr></table>	WM	Waste storage area	<table border="1"><tr><td>SP</td></tr></table>	SP	Stockpile
I									
WM									
SP									
—GB— Gravel bag berm	<table border="1"><tr><td>CW</td></tr></table>	CW	Concrete washout	<table border="1"><tr><td>E/E</td></tr></table>	E/E	Stabilized entrance/exit	→	Flow direction	
CW									
E/E									
—SF— Silt fence									